

# KARAVAN

## BOAT

**Welded Tubular Frame**  
for strength and stability

Attractive, durable  
**17-Step Powder Coat Finish**

Reliable  
**ShortFree™**  
Lighting  
and **Sure-Lube**  
systems

**QuietTow™** and **SwayControl™**  
engineering for carefree towing

**KKB-1800-70**



**SLT-5800-78**



**KKRT-4800-78**




**KKB-2400-78**




# Find The Right Trailer In 3 Easy Steps

## 1. Measure the Transom-To-Bow-Eye Length



## 2. Measure the Bottom Width



## 3. Calculate Carrying Capacity

$$\text{Carrying capacity} = \left[ \text{Boat weight including motor (lb)} + \left( \text{Fuel capacity (gal)} \times 6.3 \text{ lb / gal} \right) \right] \times \begin{cases} 1.07 & \text{if max passenger capacity} \leq 6 \\ 1.10 & \text{if max passenger capacity} > 6 \end{cases}$$

| SPECS         |                   | BOAT            |                    |                  | TRAILER        |               |                       |                |         |                   |              |                 |
|---------------|-------------------|-----------------|--------------------|------------------|----------------|---------------|-----------------------|----------------|---------|-------------------|--------------|-----------------|
|               |                   | Max Boat Length | Transom to Bow Eye | Max Bottom Width | Overall Length | Overall Width | Width Between Fenders | Trailer Weight | GVWR    | Carrying Capacity | Tire Size    | Hitch Ball Size |
| STEEL BUNK    | KBE-1250/900-46   | 199"            | 95-182"            | 47"              | 217"           | 59"           | 47"                   | 250 lb         | 1500 lb | 1250 lb           | 4.80 x 12B   | 2"              |
|               | KB-1250-56        | 204"            | 106-188"           | 57"              | 222"           | 73"           | 57"                   | 335 lb         | 1585 lb | 1250 lb           | 5.30 x 12C   | 2"              |
|               | KB-1470-56        | 204"            | 106-188"           | 57"              | 222"           | 73"           | 57"                   | 335 lb         | 1805 lb | 1470 lb           | ST175/80D13B | 2"              |
|               | KBL-1500-56       | 234"            | 133-217"           | 57"              | 252"           | 73"           | 57"                   | 325 lb         | 1825 lb | 1500 lb           | ST175/80D13B | 2"              |
|               | KDB-1500-71       | 174"            | 106-156"           | 68"              | 192"           | 85"           | 68"                   | 410 lb         | 1910 lb | 1500 lb           | ST175/80D13B | 2"              |
|               | KCB-1800-60       | 210"            | 163-194"           | 63"              | 228"           | 79"           | 63"                   | 385 lb         | 2185 lb | 1800 lb           | ST175/80D13B | 2"              |
|               | KKB-1800-70       | 221"            | 180-194"           | 72"              | 239"           | 90"           | 72"                   | 420 lb         | 2220 lb | 1800 lb           | ST175/80D13B | 2"              |
|               | KKB-2400-78       | 225"            | 177-191"           | 80"              | 243"           | 99"           | 80"                   | 550 lb         | 2950 lb | 2400 lb           | ST185/80D13C | 2"              |
|               | KCB-2400-82       | 223"            | 188-203"           | 85"              | 241"           | 102"          | 85"                   | 525 lb         | 2925 lb | 2400 lb           | ST185/80D13C | 2"              |
|               | KCB-3100-DB-78    | 274"            | 203-237"           | 80"              | 292"           | 100"          | 80"                   | 620 lb         | 3720 lb | 3100 lb           | ST215/75D14C | 2"              |
|               | KCBT-4800-TDB-78  | 274"            | 204-238"           | 80"              | 292"           | 100"          | 80"                   | 1095 lb        | 5895 lb | 4800 lb           | ST215/75D14C | 2"              |
|               | KKBT-4800-DB-78   | 279"            | 208-241"           | 80"              | 297"           | 99"           | 80"                   | 920 lb         | 5720 lb | 4800 lb           | ST215/75D14C | 2"              |
| STEEL ROLLER  | KKBT-5400-DB-78   | 306"            | 218-284"           | 80"              | 324"           | 99"           | 80"                   | 1020 lb        | 6420 lb | 5400 lb           | ST215/75D14C | 2"              |
|               | KR-1500-56        | 207"            | 106-189"           | 57"              | 225"           | 73"           | 57"                   | 325 lb         | 1825 lb | 1500 lb           | 5.30 x 12C   | 2"              |
|               | KKR-3100-DB-78-S  | 248"            | 176-210"           | 80"              | 266"           | 99"           | 80"                   | 630 lb         | 3730 lb | 3100 lb           | ST215/75D14C | 2"              |
| ALUMINUM BUNK | KKRT-4800-DB-78   | 272"            | 221-234"           | 80"              | 290"           | 99"           | 80"                   | 980 lb         | 5780 lb | 4800 lb           | ST215/75D14C | 2"              |
|               | SL-1700-70        | 225"            | 166-203"           | 77"              | 243"           | 92"           | 77"                   | 500 lb         | 2200 lb | 1700 lb           | ST175/80D13B | 2"              |
|               | SL-2450-74        | 224"            | 181-193"           | 82"              | 242"           | 97"           | 82"                   | 510 lb         | 2960 lb | 2450 lb           | ST185/80D13C | 2"              |
|               | SL-4100-DB12-78   | 256"            | 199-214"           | 84"              | 274"           | 102"          | 84"                   | 841 lb         | 4941 lb | 4100 lb           | ST225/75D15D | 2"              |
|               | SLT-5800-TDB10-78 | 308"            | 236-286"           | 82"              | 326"           | 102"          | 82"                   | 1270 lb        | 7070 lb | 5800 lb           | ST215/75D14C | 2"              |
|               | SLT-8600-TDB12-78 | 327"            | 272-288"           | 81"              | 345"           | 102"          | 81"                   | 1320 lb        | 9920 lb | 8600 lb           | ST225/75D15D | 2-5/16"         |

## FEATURES

### SwayControl™ Engineering

Welded tubular frame and adjustable axle

### Durable and Attractive High Quality Finish

Choose either our galvanized or black powder coat

### Step Fender / Swing Tongue

Standard on most models

### Optional Low Maintenance Disc Brakes

Both single axle and tandem axle disc brakes available

### QuietTow™ Componentry

Less noise on spring axle models via nylon bushings

### High Reliability ShortFree™ Lighting System

Fully grounded and all plug (no ScotchLoks); wiring is concealed

### Sure-Lube Wheel Bearing Grease System

Allows quick and clean greasing for easy maintenance

### Coated Self-Coiling Safety Cables

Cables coil out of the way when not in use

# KARAVAN

PO Box 27 Fox Lake, WI 53933 fx 920.928.6201  
www.karavantrailers.com