

# KARAVAN

## PERSONAL WATERCRAFT

**Welded Tubular Frame**  
for strength and stability

Attractive, durable  
**Galvanized, Powder Coat, and Aluminum Options**

**QuietTow™**  
and **SwayControl™**  
engineering for carefree towing

Reliable  
**ShortFree™ Lighting**  
and **Sure-Lube** systems



WCE-1250-46-L TRSN



WCE-1250-46-L TRSN



WC-2450-84-L



WCA-2600-82



# Find The Right Trailer For You

## Calculate Carrying Capacity

$$\text{Carrying capacity} = \left[ \text{Personal watercraft weight (lb)} + \left( \text{Fuel capacity (gal)} \times 6.3 \text{ lb / gal} \right) \right] \times \begin{matrix} 1 \text{ for single PWC} \\ 2 \text{ for double PWC} \end{matrix}$$

| SPECS        |                 | # of Places | Overall Length | Overall Width | Trailer Weight | GVWR    | Carrying Capacity | Tire Size    | Hitch Ball Size |
|--------------|-----------------|-------------|----------------|---------------|----------------|---------|-------------------|--------------|-----------------|
| STEEL SINGLE | WCE-900-40      | 1           | 149"           | 56"           | 210 lb         | 1110 lb | 900 lb            | 4.80 X 8B    | 2"              |
|              | WCE-1250-40     | 1           | 149"           | 56"           | 212 lb         | 1462 lb | 1250 lb           | 4.80 X 12B   | 2"              |
|              | WCE-1250-46     | 1           | 153"           | 61"           | 229 lb         | 1479 lb | 1250 lb           | 4.80 X 12B   | 2"              |
|              | WCE-1250-46-L   | 1           | 171"           | 61"           | 255 lb         | 1505 lb | 1250 lb           | 4.80 X 12B   | 2"              |
|              | WCE-1500-46     | 1           | 171"           | 66"           | 275 lb         | 1775 lb | 1500 lb           | 5.30 X 12C   | 2"              |
| STEEL DOUBLE | WC-1250-86      | 2           | 149"           | 102"          | 340 lb         | 1590 lb | 1250 lb           | 4.80 X 12B   | 2"              |
|              | WC-2200-84-S /L | 2           | 184"           | 100"          | 475 lb         | 2675 lb | 2200 lb           | ST175/80D13C | 2"              |
|              | WC-2450-84-S/L  | 2           | 184"           | 100"          | 485 lb         | 2935 lb | 2450 lb           | ST185/80D13C | 2"              |
|              | WC-2800-84-L    | 2           | 184"           | 100"          | 531 lb         | 3331 lb | 2800 lb           | ST185/80D13C | 2"              |
| ALUMINUM     | WCA-1250-46-L   | 1           | 172"           | 60"           | 250 lb         | 1500 lb | 1250 lb           | 4.80 x 12B   | 2"              |
|              | WCA-2600-82     | 2           | 184"           | 101"          | 360 lb         | 2960 lb | 2600 lb           | ST185/80D13C | 2"              |

## FEATURES

### SwayControl™ Engineering

Welded tubular frame and adjustable axle

### Durable and Attractive High Quality Finish

Choose either our galvanized or black powder coat

### Convenient Step Fender

Standard on many models

### Low Profile Crossmember Design

Standard on most models for better launchability / retrievability

### QuietTow™ Componentry

Less noise on spring axle models via nylon bushings

### High Reliability ShortFree™ Lighting System

Fully grounded and all plug (no ScotchLoks); wiring is concealed

### Sure-Lube Wheel Bearing Grease System

Allows quick and clean greasing for easy maintenance

### Coated Self-Coiling Safety Cables

Cables coil out of the way when not in use

# KARAVAN

PO Box 27 Fox Lake, WI 53933 fx 920.928.6201  
www.karavantrailers.com